




Model ACB-4E\_

Available in 1.2 and 1.8 meter models (4' and 6').  
Shown with optional stand.

# OptiMAIR™

## Vertical Laminar Flow Cabinet

The World's Quietest and Safest Choice for Sample Protection Needs




### KEY BENEFITS:

- Sliding Sash with Ergonomic Handle
- ULPA Filter (ISO Class 3 Work-zone)
- Sentinel™ Silver Microprocessor Control System
- German-made ebm-papst® Centrifugal Motor
- Isocide™ Antimicrobial Powder Coating
- Stable and Self-compensating Airflow

**ESCO**  
SCIENTIFIC

# OptiMair™ Vertical Laminar Flow Cabinet

Provides reliable protection of samples and work processes through the continuous supply of clean laminar air blowing across the work zone.




## High Performance Motor Fan

- German made ebm-papst® permanently lubricated motor fan.
- Provides a smooth, quiet, and vibration-free operation.
- Compact design with completely integrated assembly which optimizes motor cooling.




## ULPA Filter

- 10x filtration efficiency with ISO class 3 work zone instead of industry-standard ISO class 5.
- Efficiency of >99.999% at particle size between 0.1 to 0.2 µm.



## Sliding Sash Window

- Sliding sash with ergonomic handle
- UV resistant tempered glass



**Air Cleanliness Standards**  
(ISO 14644-1, Air Cleanliness Particle Limits  
(No. of Particles / m<sup>3</sup>))

Particle Size (µm)	Cleanliness Class					
	Class 1	Class 2	Class 3	Class 4	Class 5	Class 6
0.1	10	100	1000	10000	100000	1000000
0.2	2	24	237	2370	23700	237000
0.3	-	10	102	1020	10200	102000
0.5	-	4	35	352	3520	35200
1.0	-	-	8	83	835	8320
5.0	-	-	-	-	29	293

## Superior Air Cleanliness

All Esco laminar flow cabinets with ULPA filter provide ISO class 3 air cleanliness within the work zone per ISO 14644.1, significantly cleaner than the usual ISO class 5 on cabinets offered by the competition.

	Cabinet Performance	Air Quality	Filtration	Electrical Safety
Standards Compliance	IEST-RP-CC002.2, Worldwide	ISO 14644.1, Class 3, Worldwide AS 1386 Class 1.5, Australia JIS B9920, Class 3, Japan	EN-1822 (H14), Europe IEST-RP-CC001.3, Worldwide IEST-RP-CC007, Worldwide IEST-RP-CC034.1, Worldwide	IEC61010-1, Worldwide EN 61010-1, Europe UL61010-1, USA CAN/CSA-22.2, No.61010-1

## Sentinel™ Silver Microprocessor Controller

- Supervises all cabinet functions with large display monitor and operational parameters.
- Centered and angled down placement for easy reaching and viewing.



## AutoPurge™ Slots

- Eliminates air turbulence and possible dead air corners in the work-zone giving more stability in the airflow.




## Work Top

- Raised at the front edge to contain any accidental liquid spills.



## Isocide™ Antimicrobial Powder Coating


- Silver-ion impregnated powder coat
- Inhibits microbial growth to improve safety



OptiMair™ Vertical Laminar Flow Cabinet  
Model: ACB-4E\_

## Guide to Models


ACB -							
1st Placeholder	2nd Placeholder	3rd Placeholder		4th Placeholder			
Product Line	Width	Control		Electrical			
OptiMair™	ACB	4 feet	4	Sentinel™ Silver	E	230 VAC, 50 Hz	1
		6 feet	6			115 VAC, 50/60 Hz	2
						230 VAC, 60 Hz	3



## Cabinet Filtration System

- Air is drawn from the top of the cabinet and will pass through the pre-filter. The ebm-papst® motor fan will then facilitate air movement towards the ULPA filter to produce a stream of clean laminar air within the work zone, diluting and flushing contaminants present in the interior. The purified air travels in a vertical, unidirectional stream across the front and back of the work-zone.
- A nominal filter face velocity of 0.30 m/s (60 fpm) ensures that there are enough air changes within the enclosed area of the cabinet to maintain cleanliness.

## OptiMair™ Vertical Laminar Flow Engineering Drawing



## Applications

Microbiology (Non-pathogenic microorganisms)

Plant and Mammalian Cell Culture

Forensics

Biotechnology (e.g. PCR)

Compounding non-hazardous sterile products

Medical Device Industry

Semiconductor Assembly

## General Specifications, OptiMair™ Vertical Laminar Flow Cabinet

Model		ACB-4E1 2120765	ACB-6E1 2120769
		ACB-4E2 2120781	ACB-6E2 2120782
		ACB-4E3 2120778	ACB-6E3 2120780
Nominal Size		1.2 meter (4')	1.8 meters (6')
External Dimensions (W x D x H)	Without Base Stand	1340 x 620 x 983 mm (52.8" x 24.4" x 38.7")	1950 x 620 x 983 mm (76.8" x 24.4" x 38.7")
	With Optional Base Stand, 711 mm (28") type	1340 x 620 x 1694 mm (52.8" x 24.4" x 66.7")	1950 x 620 x 1694 mm (76.8" x 24.4" x 66.7")
Internal Work Area, Dimensions (W x D x H)		1270 x 524 x 570 mm (50.0" x 20.6" x 22.4")	1880 x 524 x 570 mm (74.0" x 20.6" x 22.4")
Usable Work Zone		0.67 m <sup>2</sup> (7.2 sq.ft.)	0.99 m <sup>2</sup> (10.7 sq.ft.)
Initial Airflow Velocity		0.3 m/s (60 fpm)	
Air Volume		566 m <sup>3</sup> /h (333 cfm)	850 m <sup>3</sup> /h (500 cfm)
ULPA Filter Typical Efficiency		>99.999% for particles size between 0.1 to 0.2 μm	
Sound Emission Per IEST-RP-CC002.2*		<61 dBA	<63 dBA
Fluorescent Lamp Intensity At Zero Ambient		>1000 Lux (74 foot candles)	
Cabinet Construction	Main Body	1.2 mm / 0.05" / 18 gauge electro-galvanized steel with white oven-baked epoxy powder-coated finish	
	Work Zone	1.2 mm (0.05") 18 gauge stainless steel, grade 304, 4B finish	
	Side Walls	Tempered glass	
Electrical Power Rating 1: 220-240 VAC, 50Hz, 1Ø	Cabinet Full Load Amps (FLA)	6.3 A	6.5 A
	Optional Outlets FLA	5 A	
	Cabinet Nominal Power	275 W	285 W
	Cabinet BTU	938	972
Electrical Power Rating 3: 220-240 VAC, 60Hz, 1Ø	Cabinet Full Load Amps (FLA)	1.3 A	1.6 A
	Optional Outlets FLA	5 A	
	Cabinet Nominal Power	198 W	
	Cabinet BTU	676	
Net Weight**		140 kg (308 lbs)	182 kg (400 lbs)
Shipping Weight**		178 kg (392 lbs)	231 kg (508 lbs)
Shipping Dimensions, Maximum (W x D x H)**		1430 x 749.5 x 1233 mm (56.3" x 29.5" x 48.5")	2110 x 749.5 x 1233 mm (83.1" x 29.5" x 48.5")
Shipping Volume, Maximum**		1.32 m <sup>3</sup> (46.6 cu.ft)	1.95 m <sup>3</sup> (68.9 cu.ft)

\*Noise reading in open field condition/ anechoic chamber.

\*\*Cabinet only; excludes optional stand.


## Accessories for OptiMair™ Vertical Laminar Flow Cabinet

Model	4 ft.	6 ft.
UV Lamp	UV-30A (5170255)	
Electrical Outlet	EO	
Support Stand with Caster Wheels	SPC-4E0 (5131346)	SPC-6E0 (5131347)
	SPC-4F0 (5131355)	SPC-6F0 (5131356)
Supports Stand with Levelling Feet	SAL-4E0 (5131349)	SAL-6E0 (5131350)
	SAL-4F0 (5131352)	SAL-6F0 (5131353)
Service Fixtures	SF-1G50 (5170015)	
	SF-IV50 (5170004)	
	SF-1N50 (5170012)	
	SF-1A50 (5170007)	
	SF-1W50 (5170009)	
	SF-2U50 (5170019)	
	CU-Pipe (5170026)	
IV Bar	IV-XXX-XXX (Specify model when ordering)	

*Note: 2 Universal (European/ American/ Japanese / Asia-Pacific) electrical outlets are standard on all OptiMair™ Cabinets.*




**UV Lamp**



**Service Fixture**



**Electrical Outlet**



**Stainless Steel IV Bar**



**Support Stand with Levelling Feet (28 and 34 in)**



**Support Stand with Caster Wheels**



providing

reliable product protection

and

energy-efficient technology



*Airstream® Gen 3  
Horizontal Laminar Flow Cabinet  
Model: LHG-4AG*



*Airstream® Gen 3  
Vertical Laminar Flow Cabinet  
Model: LVG-4AG*



*Airstream® Horizontal Laminar Flow Cabinet  
for Plant Tissue Culture  
Model: LHG-4DS*




*Enterprise® Laminar Flow Straddle Units,  
Model EQU/06-ESUS*

#Escogoesgreen

**ESCO**  
SCIENTIFIC


# ESCO LIFESCIENCES GROUP

42 LOCATIONS IN 21 COUNTRIES ALL OVER THE WORLD



- Global Offices
- Joint Ventures
- Licensee
- Distributors
- Factories
- R&D Centers
- Regional Distribution Centers

Join us on Social Media and Download our Apps!



Filtra Check App  
The World's First Chemical  
Evaluation App



Esco Social Media  
and Apps



Esco Micro Pte. Ltd. • 21 Changi South Street 1 • Singapore 486 777  
Tel +65 6542 0833 • Fax +65 6542 6920 • mail@escolifesciences.com  
www.escolifesciences.com

Esco Technologies, Inc. • 903 Sheehy Drive, Suite F, Horsham, PA 19044, USA  
Tel: +1 215-441-9661 • Fax 484-698-7757  
eti.admin@escolifesciences.com

Esco Lifesciences Group Offices: Bangladesh | China | Denmark | Germany | Hong Kong | India | Indonesia | Italy | Japan | Lithuania  
| Malaysia | Myanmar | Philippines | Russia | Singapore | South Africa | South Korea | Taiwan | Thailand | UAE | UK | USA | Vietnam